



ADHESIVES & SEALANTS

Silaprene adhesive/sealant

SILAPRENE is the **best adhesive and waterproof sealant available on the market**. SILAPRENE can be applied on aluminum, steel, fibreglass and most plastic surfaces, tiles, marble, ceramic, concrete, brick, rubber, as well as on wood and its derivatives.

Characteristics.

- Requires no **primer prior** to use.
- Single component elastomeric adhesive and caulking sealant.
- Resistant to water, sun, ice, snow, heat, cold, salt, grease, oil, and most chemicals.
- Resistant to a wide range of temperatures from -50°C to 120°C (-60°F to 250°F).
- Procures a flexibility which permits resistance to shocks, vibrations and constraints.
- Paintable.
- Bonds to itself.

Prod. #	Supplier #	Colors	Shelf life	Cartridge	Case
642-2009	M6326	Black	7 months	312 ml	24 tubes
642-2016	M6325	Grey	7 months	312 ml	24 tubes
642-2023	M6324	Off-white	7 months	312 ml	24 tubes
642-2030	M6330	Aluminum	7 months	312 ml	24 tubes
642-2048*	M6328	Super-white	9 months	312 ml	24 tubes

* Recommended as sealant only.

Distributed in Canada exclusively by Faucher



Silaprene transportation

SILAPRENE TRANSPORTATION adhesive/sealant is a multi-purpose product designed for bonding and sealing metal, fiberglass, FRP and wood.

Being a very flexible material, it can maintain joint integrity while absorbing shock and vibration, as well as the differences in thermal expansion and contraction.

- High resistance to UV light, heat, moisture, as well as oils, snow, ice and road salt.

Prod. #	Supplier #	Colors	Cartridge	Case
642-2231	DC12084	Grey	300 ml	24
642-2249	DC12231	Super-white	300 ml	24

Properties:

SILAPRENE TRANSPORTATION	
Base polymer	Polychloroprene
Solids (%)	52
Temp. Range (°C) Solvents	-29 to 121
Shelf Life	9 months
Paintable	Yes
Sandable	Yes
Primer Required	No
High UV Resistance	Yes
Colors	2

Distributed in Canada exclusively by Faucher



REV. 01/2011

Silaprene Solidseal

SILAPRENE SOLIDSEAL adhesive/sealant has been specifically developed for use in the construction and repair of trailers, trucks, buses, trains, RV utility bodies, van conversions and specialty vehicles.

Due to its exceptional elastic properties, it can be used in floor bonding applications such as sub-flooring to metal cross members, butt joints and more.

This VOC compliant, very versatile product has excellent adhesion to pre-painted metals, plywood, glass, aluminum, steel, SMC, RIM, FRP and other plastics and composites.

A primer is not required, therefore reducing the labor time for application.

Prod. #	Supplier #	Colors	Cartridge	Case
642-2256	DC12176	White	304 ml	24
642-2263	DC12154	Grey	304 ml	24

Properties:

SILAPRENE SOLIDSEAL	
Base polymer	Polyurethane
Solids (%)	96
Temp. Range (°C) Solvents	-40 to 93
Shelf Life	1 year
Paintable	Yes
Sandable	Yes
Primer Required	No
High UV Resistance	Yes
Colors	3

Distributed in Canada exclusively by Faucher



Silaprene Solidbond

SILAPRENE SOLIDBOND is a one component, high strength bonding adhesive with excellent sealant properties that provides a permanently elastic bond to most substrates. SOLIDBOND is a moisture cured, non sag system, specifically developed for the fabrication and repair of trailers, trucks, buses, trains, RV utility bodies, van conversions and specialty vehicles.

SILAPRENE SOLIDBOND

Prod. #	Supplier #	Colors	Cartridge	Case
642-2626	DC12250	White	300 ml	12

Properties:

SILAPRENE SOLIDBOND	
Base polymer	Polyurethane
Solids (%)	98
Temp. Range (°C) Solvents	-40 to 93
Shelf Life	1 year
Paintable	Yes
Sandable	Yes
Primer Required	No*
High UV Resistance	Yes
Colors	2

*Cures faster with primer. Apply 1 to 3 hrs prior to the application of Solidbond.

Distributed in Canada exclusively by Faucher



REV. 01/2011

Faucher general purpose silicone sealants

General purpose RTV sealant for bonding and sealing applications formed in place gasketing, space filling, etc. Will not sag or run.

Temperature range:
-85 degree F to 450 degree F.
Tack free time 15-20 minutes.

Prod. #	Colors	Cartridge	Case
642-0474	Clear	300 ml	24
642-0435	White	300 ml	24
642-0442	Black	300 ml	24
642-0467	Aluminum	300 ml	24

Sold per case only.



General purpose silicone sealant

Nuflex 302

General purpose RTV sealant for bonding and sealing applications formed in place gasketing, space filling, etc. Will not sag or run.

Temperature range:
-85 degree F to 450 degree F.
Tack free time 15-20 minutes.

Prod. #	Color	Tube	Case
642-0107	Clear	80 ml	24

Sold per case only.



Hi temperature silicone sealant

Nuflex 302

Will not sag or run.

Can be used on industrial furnaces, doors, wood, dryers etc.

Temperature range:
-85 degree F to 600 degree F
Tack free: 15-20 minutes

Prod. #	Color	Cartridge	Case
642-0153	Red	300 ml	24

Sold per case only.



Butyl-based sealant

Manus-Bond 501-A

Rapidly forms a skin.
Can be painted.
Good bonding.
Remains flexible.
Shelf life 12 months.

Prod. #	Color	Cartridge	Case
641-1254	Grey	312 ml	36



Butyl tape sealants

ET-440-II

A grey butyl base tape which always remains soft. Very good adhesion. Used for glass-setting, lapping joints, as an insulator against galvanic reactions, etc. Good resistance to immersion. Shelf life 12 months.

Prod. #	Dimensions	Roll	Case
643-1042	1/16" x 1/4"	50'	1300'
643-1067	1/16" x 1/2"	50'	1000'
643-1074	1/16" x 3/4"	50'	700'
643-1081	1/16" x 1"	50'	500'
643-1099	1/8" x 1/2"	25'	500'
643-1109	1/8" x 3/4"	25'	350'
643-0017	1/8" x 1"	25'	250'

Joining compound tapes are in rolls, on a non-stretchable paper backing. This allows for even thickness all along the joint and eliminates clean-ups.

Some parts may be lead time items. Consult our sales department for availability.



Sold per case only.

Elastomer tape sealants

ET-675

Elastomeric type black rubber tape with very high adhesion. Water resistant. Many applications such as bonding roof sheeting, sealing water pipe joints in refrigeration, etc. Shelf life 12 months.

Prod. #	Dimensions	Roll	Case
643-1130	1/8" x 1/2"	25'	400'
643-1123	1/8" x 3/4"	25'	625'

Some parts may be lead time items. Consult our sales department for availability.




Sold per case only.

Duct tape

Metallic grey canvas tape. Used as insulation between dissimilar metals to prevent electrolysis, as well as to seal air ducts.

Prod. #	Width	Length
626-0044	48 mm — 1 7/8"	55 m

Some parts may be lead time items. Consult our sales department for availability.



Aluminum foil duct tape

Highly adhesive backing
To seal air ducts.
Also used to repair a leaking roof temporarily.

Prod. #	Thickness	Width	Length
626-0943	0.015	4"	100'



REV. 01/2014

Weatherstrip adhesive

Prod. #: **642-0026**

Black weatherstrip adhesive.
 Tube: 150 ml
 Case: 12 units

Some parts may be lead time items.
 Consult our sales department for availability.



Adhesive spray

Prod. #: **642-0058**

Very high adhesion glue without CFC.
 Quick bonding.
 Ideal to glue rubber foam, fabric, wood, paper and plastic.
 14 fl. oz (397 g) aerosol spray
 Case: 12 units



Caulking gun

Prod. #: **640-0005**

Industrial quality heavy duty
 For standard 300-315 ml cartridges.
 Ratio: 12:1



REV. 04/2018


LPS1

Prod. #: 940-1092

Greaseless lubricant

Can be used even for delicate mechanisms. Resists the accumulation of dust and dirt. Dries out electronic and electrical systems in a few seconds. Penetrates and rapidly loosens frozen parts. Non-staining and will not damage rubber, paint or plastic.

- Approved by Agriculture Canada for use in food processing plants.
- Inverta Spray Valve allows one to spray in an upright or inverted position.
- 312 g aerosol spray.
- Also available in 3.78 l, 18.93 l, 208 l and 591 ml trigger spray containers from LPS.



Sold per case of 12 only.

LPS2

Prod. #: 940-1102

Industrial strength lubricant

Multi-purpose lubricant leaves a medium deposit of oil. Prevents rust. Rapidly penetrates rust and frozen components. Will not damage rubber, paint or plastic. Provides up to one year of protection.

- Inverta Spray Valve allows one to spray in an upright or inverted position.
- Approved by Agriculture Canada for use in food processing plants.
- 312 g aerosol spray.
- Also available in 3.78 l, 18.93 l, 208 l and 591 ml trigger spray containers from LPS.



Sold per case of 12 only.

TKX

Prod. #: 940-1046

Lubricant, penetrant, all-purpose protectant

- Leaves a light coating of oil.
- Can be used inside and outside.
- Displaces moisture.
- Loosens rusted or frozen parts.
- Protects against corrosion.
- Flash point 175°F.

- Does not contain chlorinated solvents or silicone.
- Does not damage fabrics, rubber, paints or plastics.
- Inverta Spray Valve.
- 312 g aerosol spray.
- Also available in 3.78 l, 18.93 l and 208 l containers from LPS.



Sold per case of 12 only.

LPS-3 Heavy-duty rust inhibitor

Prod. #: 940-1060

Some parts may be lead time items. Consult our sales department for availability.



Sold per case of 12 only.

Forms a waxy antirust coating which provides excellent protection against rust and corrosion. Resistant to humidity. Does not damage rubber, paint or plastics.

- Protects up to two-year.
- Approved by Agriculture Canada for use in food processing plants.
- Meets the following specifications:
 - Boeing BMS-3-23F Type II
 - MIL-C-0083933A, para. 3.2-3.16
 - MIL-C-16173D Grade 2 Class I
 - DMS 2150
 - Airbus TN A. 007.10138 Type 1 Grade 2
- 312 g aerosol spray.
- Also available in 3.78 l, 18.93 l, 208 l and 591 ml trigger spray containers from LPS.

Cold galvanize

Prod. #: 940-1085

Sold per case of 12 only.



Some parts may be lead time items. Consult our sales department for availability.

- Galvanized, 95% pure zinc coating.
- Can be used on rusted metal.
- Does not yellow.
- Does not chalk.
- Does not peel.
- 397 g aerosol spray.
- Approved by Agriculture Canada for use in food processing plants.

REV. 04/2013

A large grid of 20 columns and 30 rows for taking notes. The grid is composed of thin, light gray lines forming a series of small squares. The grid is contained within a rounded rectangular border.

□ = 1/4"